

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications

11.1 contains Switched Access Service Options (which are comprised of Interface Groups, Supervisory Signaling, Entry Switch Receive Level and Local Transport Termination) and Transmission Specifications. 11.2 describes Special Access Service Network Channel (NC) codes and Network Channel Interface (NC) codes.

11.1 Switched Access Service

Ten Interface Groups are provided for terminating the Transport at the customer's designated premises. Each Interface Group provides a specified premises interface (e.g., two-wire, four-wire, DS1, etc.). Where transmission facilities permit, the individual transmission path between the customer's designated premises and the first point of switching may, at the option of the customer, be provided with optional features as set forth in 11.1.1 following.

As a result of the customer's access order and type of Telephone Company transport facilities serving the customer designated premises, the need for signaling conversions or two-wire to four-wire conversions, or the need to terminate digital or high frequency facilities in channel bank equipment may require that Telephone Company equipment be placed at the customer designated premises. For example, if a voice frequency interface is ordered by the customer and the Telephone Company facilities serving the customer designated premises are digital, then Telephone Company channel bank equipment must be placed at the customer designated premises in order to provide the voice frequency ordered by the customer.

11.1.1 Transport Interface Groups

Interface Groups are combinations of technical parameters which describe the Telephone Company handoff at the point of termination at the customer designated premises. The technical specifications concerning the available interface groups are set forth in (A) through (D) following.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: Alvin Hamilton Title President

AECA 11-1

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

Interface Group 1 is provided with Type C Transmission Specifications, as set forth in 11.1.2(C) following, and Interface Groups 2 through 10 are provided with Type A or B Transmission Specifications, as set forth respectively in 11.1.2(E) and (F) following, depending on the Feature Group and whether the Access Service is routed directly or through an access tandem. All Interface Groups are provided with Data Transmission Parameters.

Only certain premises interfaces are available at the customer designated premises. The premises interfaces associated with the Interface Groups may vary among Feature Groups.

(A) Interface Group 1

Interface Group 1, except as set forth in the following, provides two-wire voice frequency transmission at the point of termination at the customer designated premises. The interface is capable of transmission of voice and associated telephone signals within the frequency bandwidth of approximately 300 to 3000 Hz.

Interface Group 1 is not provided in association with FGC and FGD when the first point of switching is an access tandem. In addition, Interface Group 1 is not provided in association with FGB, FGC or FGD when the first point of switching provides only four-wire terminations.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: Steve J. JansenTitle President

AECA 11-2

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(A) Interface Groups 1 (Cont'd)

The transmission path between the point of termination at the customer designated premises and the first point of switching may be comprised of any form or configuration of plant capable of and typically used in the telecommunications industry for the transmission of voice and associated telephone signals within the frequency bandwidth of 300 to 3000 Hz.

The interface is provided with loop supervisory signaling. When the interface is associated with FGA, such signaling will be loop start or ground start signaling. When the interface is associated with FGB, FGC, or FGD, such signaling except for two-way calling which is E&M signaling, will be reverse battery signaling.

(B) Interface Group 2

Interface Group 2 provides four-wire voice frequency transmission at the point of termination at the customer designated premises. The interface is capable of transmission of voice and associated telephone signals within the frequency bandwidth of approximately 300 to 3000 Hz.

The transmission path between the point of termination at the customer designate premises and the first point of switching may be comprised of any form or configuration of plant capable of and typically used in the telecommunications industry for the transmission of voice and associated telephone signals within the frequency bandwidth of approximately 300 to 3000 Hz.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Steve Humble

Title President

AECA 11-3

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(B) Interface Group 2 (Cont'd)

The interface is provided with loop supervisory signaling. When the interface is associated with FGA, such signaling will be loop start or ground start signaling. When the interface is associated with FGB, FGC, or FGD, such signaling, except for two-way calling which is E&M signaling, will be reverse battery signaling.

(C) Interface Groups 3 through 5

Interface Groups 3 through 5 provide analog transmission at the point of termination at the customer designated premises. The various interfaces are capable of transmitting electrical signals at the frequencies illustrated following, with the capability to channelize voice frequency transmission paths. Certain frequencies within the bandwidth of the Interface Groups are reserved for Telephone Company use, e.g., pilot and carrier group alarm tones. Before the first point of switching, the Telephone Company will provide multiplex equipment to derive the transmission paths of frequency bandwidth of approximately 300 to 3000 Hz.

The interfaces are provided with individual transmission path SF supervisory signaling.

<u>Interface Group Identification No.</u>	<u>Transmission Frequency Bandwidth</u>	<u>Analog Hierarch Level</u>	<u>Maximum No. of Channelized Voice Freq. Trans. Paths</u>
3	60-108 kHz	Group	12
4	312-552 kHz	Supergroup	60
5	564-3084 kHz	Mastergroup	600

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Alvin Humler

Title

President

AECA 11-4

RECEIVED

NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(D) Interface Groups 6 through 10

Interface Groups through 10 provide digital transmission at the point of termination at the customer designated premises. The various interfaces are capable of transmitting electrical signals at the nominal bit rates illustrated following, with the capability to channelize voice frequency transmission paths. Before the first point of switching, when analog switching utilizing analog terminations is provided, the Telephone Company will provide multiplex and channel bank equipment to derive transmission paths of a frequency bandwidth of approximately 300 to 3000 Hz. When digital switching or analog switching with digital carrier terminations is provided, the Telephone Company will provide, at the first point of switching, a DS1 signal(s) in D3/D4 format.

The interfaces are provided with individual transmission path bit stream supervisory signaling.

<u>Interface Group Identification No.</u>	<u>Nominal Bit Rate (Mbps)</u>	<u>Digital Hierarchy Level</u>	<u>Max No. of Channelized Voice Freq. Trans. Paths</u>
6	1.544	DS1	24
7	3.152	DS1C	48
8	6.312	DS2	96
9	44.736	DS3	672
10	274.176	DS4	4032

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective

January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Alice Humlan

Title

President

AECA 11-5

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(E) Transport Optional Features

Where transmission facilities permit, the Telephone Company will, at the option of the customer, provide the following features in association with Transport. An Access Order Charge is applicable on a per order basis when nonchargeable optional features are added subsequent to the installation of service.

- Customer Specified Entry Switch Receive Level

Customer Specified Entry Switch Receive Level allows the customer to specify the receive transmission level at the first point of switching. The range of transmission levels which may be specified is described in Technical Reference TR-NPL-000334. This feature is available with Interface Groups 2 through 10 for Feature Groups A and B.

- Customer Specification of Transport Termination

Customer Specification of Transport Termination allows the customer to specify, for Feature Group B routed directly to an end office or access tandem, a four-wire termination of the Transport at the first point of switching in lieu of a Telephone Company selected two-wire termination. This option is available only when the Feature Group B arrangement is provided with Type B Transmission Specifications.

- Supervisory Signaling

Supervisory Signaling allows the customer to order an optional supervisory signaling arrangement for each transmission path provided where the transmission parameters permit, and where signaling conversion is required by the customer to meet its signaling capability.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve J. Jumper*Title President

AECA 11-6

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(E) Transport Optional Features (Cont'd)

The Interface Groups, as described in (A) through (D) preceding, represent industry standard arrangements. Where transmission parameters permit, the customer may select the following optional signaling arrangements in place of signaling arrangements standardly associated with the Interface Groups.

- For Interface Groups 1 and 2 associated with FGB, FGC, or FGD

DX Supervisory Signaling
E&M Type I Supervisory Signaling,
E&M Type II Supervisory Signaling, or
E&M Type III Supervisory Signaling

- For Interface Group 2 associated with FGB, FGC, or FGD and in addition to the preceding.

SF Supervisory Signaling, or
Tandem Supervisory Signaling

- For Interface Groups 3 through 5

Optional Supervisory Signaling Not Available

- For Interface Groups 6 through 10

These Interface Groups may, at the option of the customer, be provided with individual transmission path SF supervisory signaling where such signaling is available in Telephone Company central offices. Generally such signaling is available only where the first point of switching provides an analog (i.e., non digital) interface to the transport termination.

Additionally, in (F) following, there is a matrix of available Premises Interface Codes as a function of Interface Group, Telephone Company Switch ~~Supervisory Signaling and Feature Group.~~

Tariff Advice No. 1 Pursuant to Orders No. 6 & 7 in Docket U-90-26
Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve J. Hambley* Title President

AECA 11-7

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(F) Available Premises Interface Codes

Following is a matrix showing premises interface codes which are available for each Interface Group. Their availability is a function of the Telephone Company switch supervisory signaling and Feature Group. For explanations of these codes, see the Parameter Codes and Options as set forth in 11.2.2(A) following.

Interface Group	Telephone Company		Premises Interface Code	Feature Group				
	Switch	Supervising Signaling		A	B	C	D	
1		LO	2LS2	X				
		LO	2LS3	X				
		GO	2GS2	X				
		GO	2GS3	X				
		LO, GO,	2DX3	X				
		LO, GO	4EA3-E	X				
		LO, GO	4EA3-M	X				
		LO, GO	6EB3-E	X				
		LO, GO	6EB3-M	X				
		RV, EA, EB, EC	2DX3		X	X	X	
		RV, EA, EB, EC	4EA3-E		X	X	X	
		RV, EA, EB, EC	4EA3-M		X	X	X	
		RV, EA, EB, EC	6EB3-E		X	X	X	
		RV, EA, EB, EC	6EB3-M		X	X	X	
		EA, EB, EC	6EC3			X	X	
		RV	2RV3-0		X	X	X	
		RV	2RV3-T		X	X	X	
	2		LO, GO	4SF2	X			
			LO, GO	4SF3	X			
			LO	4LS2	X			
		LO	4LS3	X				
		LO	6LS2	X				

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Title

President

AECA 11-8

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
 Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(F) Available Premises Interface Codes (Cont'd)

Interface Group	Telephone Company Switch Supervisory Signaling	Premises Interface Code	Feature Group			
			A	B	C	D
2 (Cont'd)	GO	4GS2	X			
	GO	4GS3	X			
	GO	6GS2	X			
	LO, GO	4DX2	X			
	LO, GO	4DX3	X			
	LO, GO	6EA2-E	X			
	LO, GO	6EA2-M	X			
	LO, GO	8EB2-E	X			
	LO, GO	8EB2-M	X			
	LO, GO	6EX2-B	X			
	RV, EA, EB, EC	4SF2		X	X	X
	RV, EA, EB, EC	4SF3		X		
	RV, EA, EB, EC	4DX2		X	X	X
	RV, EA, EB, EC	4DX3		X		
	RV, EA, EB, EC	6DX2			X	
	RV, EA, EB, EC	6EA2-E		X	X	X
	RV, EA, EB, EC	6EA2-M		X	X	X
	RV, EA, EB, EC	8EB2-E		X	X	X
	RV, EA, EB, EC	8EB2-M		X	X	X
	EA, EB, EC	8EC2-M			X	X
	RV	4RV2-0		X	X	X
	RV	4RV2-T		X	X	X
	RV	4RV3-0		X	X	
RV	4RV3-T		X	X		
3	LOG, GO	4AH5-B	X			
	RV, EA, EB, EC	4AH5-B		X	X	X
4	LO, GO	4AH6-C	X			
	RV, EA, EB, EC	4AH6-C		X	X	X
5	LO, GO	4AH6-D	X			
	RV, EA, EB, EC	4AH6-D		X	X	X

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Humbley* Title President

RECEIVED**NOV 21 1990**State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.1 Transport Interface Groups (Cont'd)

(F) Available Premises Interface Codes (Cont'd)

Interface Group	Telephone Company Switch Supervisory Signaling	Premises Interface Code	Feature Group			
			A	B	C	D
6	LO, GO	4DS9-15	X			
	LO, GO	4DS9-15L	X			
	RV, EA, EB, EC	4DS9-15		X	X	X
	RV, EA, EB, EC	4DS9-15L		X	X	X
7	LO, GO	4DS9-31	X			
	LO, GO	4DS9-31L	X			
	RV, EA, EB, EC	4DS9-31		X	X	X
	RV, EA, EB, EC	4DS9-31L		X	X	X
8	LO, GO	4DS0-63	X			
	LO, GO	4DS0-63L	X			
	RV, EA, EB, EC	4DS0-63		X	X	X
	RV, EA, EB, EC	4DS0-63L		X	X	X
9	LO, GO	4DS6-44	X			
	LO, GO	4DS6-44L	X			
	RV, EA, EB, EC	4DS6-44		X	X	X
	RV, EA, EB, EC	4DS6-44L		X	X	X
10	LO, GO	4DS6-27	X			
	LO, GO	4DS6-27L	X			
	RV, EA, EB, EC	4DS6-27		X	X	X
	RV, EA, EB, EC	4DS6-27L		X	X	X

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Steve Humlen

Title

President

AECA 11-10

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications

Descriptions of the transmission specifications available with each Feature Group as a function of the Interface Group selected by the customer, are set forth in (A) through (D) following. Descriptions of each of these Standard Transmission Specifications and the two Data Standard Transmission Parameters mentioned are set forth respectively in (E) through (G) and 11.1.3(A) and (B) following.

(A) Feature Group A

FGA is provided with either Type B or Type C Transmission Specifications. The specifications for the associated parameters are guaranteed to the first point of switching. Type C Transmission Specifications are provided with Interface Group 1 and Type B is provided with Interface Groups 2 through 10. Type DB Data Transmission Parameters are provided with FGA to the first point of switching.

(B) Feature Group B

FGB is provided with either Type B or Type C Transmission Specifications. The specifications for the associated parameters are guaranteed to the end office when routed directly or to the first point of switching when routed via an access tandem. Type C Transmission Specifications are provided with Interface Groups 1 and Type B is provided with Interface Groups 2 through 10. Type DB Data Transmission Parameters are provided with FGB to the first point of switching.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve Pankley* Title President

AECA 11-11

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(C) Feature Group C

FGC is provided with either Type B or Type C Transmission Specifications as follows:

- When routed directly to the end office either Type B or Type C is provided.
- When routed to an access tandem only Type B is provided.
- Type B or Type C is provided on the transmission path from the access tandem to the end office.

Type C Transmission Specifications are provided with Interface Group 1 when routed directly to an end office. Type B is provided with Interface Groups 2 through 10, whether routed directly to an end office or to an access tandem.

Type DB Data Transmission Parameters are provided with FGC for the transmission path between the customer designated premises and the end office when directly routed to to the end office, and between the customer designated premises and the access tandem and between the access tandem and the end office when routed via an access tandem.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve Bunker*Title President

AECA 11-12

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(D) Feature Group D

FGD is provided with either Type A, Type B or Type C Transmission Specifications as follows:

- When routed to the end office either Type B or C is provided.
- When routed to an access tandem only Type A is provided.
- Type A is provided on the transmission path from the access tandem to the end office.

Type C Transmission Specifications are provided with Interface Group 1. Type A and Type B Transmission Specifications are provided with Interface Groups 2 through 10.

Type DB Data Transmission Parameters are provided with FGD for the transmission path between the customer designated premises and the end office when directly routed to the end office. Type DA Data Transmission Parameters are provided for the transmission path between the customer designated premises and the access tandem and between the access tandem and the end office when routed via an access tandem.

(E) Type A Transmission Specifications

Type A Transmission Specifications is provided with the following parameters:

(1) Loss Deviation

The maximum Loss Deviation of the 1004 Hz loss relative to the Expected Measured Loss (EML) is ± 2.0 dB

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Title President

AECA 11-13

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(E) Type A Transmission Specifications (Cont'd)

(2) Attenuation Distortion

The maximum Attenuation Distortion in the 404 to 2804 Hz frequency band relative to the loss at 1004 Hz is -1.0 dB to +3.0 dB.

(3) C-Message Noise

The maximum C-Message Noise for the transmission path at the route miles listed is less than or equal to:

<u>Route Miles</u>	<u>C-Message Noise</u>
less than 50	32 dBrnCO
51 to 100	34 dBrnCO
101 to 200	37 dBrnCO
201 to 400	40 dBrnCO
401 to 1000	42 dBrnCO

(4) C-Notch Noise

The maximum C-Notch Noise, utilizing a -16 dBm0 holding tone, is less than or equal to 45 dBrnCO.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Steve Humlen

Title

President

AECA 11-14

RECEIVED
NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(E) Type A Transmission Specifications (Cont'd)

(5) Echo Control

Echo Control, identified as Equal Level Echo Path Loss, and expressed as Echo Return Loss and Singing Return Loss, is dependent on the routing, i.e., whether the service is routed directly from the customer's point of termination (POT) to the end office or via an access tandem. It is equal to or greater than the following:

	<u>Echo Return Loss</u>	<u>Singing Return Loss</u>
POT to Access Tandem	21 dB	14 dB
POT to End Office		
- Direct	N/A	N/A
- Via Access Tandem	16 dB	11 dB

(6) Standard Return Loss

Standard Return Loss expressed as Echo Return Loss and Singing Return Loss on two-wire ports of a four-wire point of termination shall be equal to or greater than:

<u>Echo Return Loss</u>	<u>Singing Return Loss</u>
5 dB	2.5 dB

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: Steve Pomeroy Title President

AECA 11-15

RECEIVED**NOV 21 1990**State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(F) Type B Transmission Specifications

Type B Transmission Specifications are provided with the following parameters:

(1) Loss Deviation

The maximum Loss deviation of the 1004 Hz loss relative to the Expected Measured Loss (EML) is ± 2.5 dB.

(2) Attenuation Distortion

The maximum Attenuation Distortion in the 404 to 2804 Hz frequency band relative to loss at 1004 Hz is -2.0 dB to +4.0 dB.

(3) C-Message Noise

The maximum C-Message Noise for the transmission path at the route miles listed is less than or equal to:

<u>Route Miles</u>	<u>C-Message Noise*</u>	
	<u>Type B1</u>	<u>Type B2</u>
less than 50	32 dBrnCO	35 dBrnCO
51 to 100	33 dBrnCO	37 dBrnCO
101 to 200	35 dBrnCO	40 dBrnCO
201 to 400	37 dBrnCO	43 dBrnCO
401 to 1000	39 dBrnCO	45 dBrnCO

(4) C-Notch Noise

The maximum C-Notch Noise, utilizing a -16 dBmO holding tone is less than or equal to 47 dBrnCO.

* For Feature Groups C and D only Type B2 will be provided. For Feature Group A and B, Type B1 or B2 will be provided as set forth in Technical TR-NPL-000334

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Dumbler* Title President

AECA 11-16

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(F) Type B Transmission Specifications (Cont'd)

(5) Echo Control

Echo Control, identified as Impedance Balance for FGA and FGB and Equal Level Echo Path Loss for FGC and FGD, and expressed as Echo Return Loss (ERL) and Singing Return Loss (SRL), is dependent on the routing, i.e., whether the service is routed directly from the customer's point of termination (POT) to the end office or via an access tandem. The ERL and SRL also differ by Feature Group, type of termination, and type of transmission path. They are greater than or equal to the following:

	<u>Echo Return Loss</u>	<u>Singing Return Loss</u>
POT to Access Tandem		
- Terminated in 4-Wire trunk	21 dB	14 dB
- Terminated in 2-Wire trunk	16 dB	11 dB
POT to End Office		
- Direct	16 dB	11 dB
- Via Access Tandem		
. For FGB access	8 dB	4 dB
. For FGC access (Effective 4-Wire transmission path at end office)	16 dB	11 dB
. For FGC access (Effective 2-Wire transmission path at end office)	13 dB	6 dB

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve Dumbler* Title President

AECA 11-17

RECEIVED
NOV 21 1990
State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(F) Type B Transmission Specifications (Cont'd)

(6) Standard Return Loss

Standard Return Loss, expressed as Echo Return Loss and Singing Return Loss, on two-wire ports of a four-wire point of termination shall be equal to or greater than:

<u>Echo Return Loss</u>	<u>Singing Return Loss</u>
5 dB	2.5 dB

(G) Type C Transmission Specifications

Type C Transmission Specifications are provided with the following parameters:

(1) Loss Deviation

The maximum Loss Deviation of the 1004 Hz Loss relative to the Expected Measured Loss (EML) is ± 3.0 dB.

(2) Attenuation Distortion

The maximum Attenuation Distortion in the 404 to 2804 Hz frequency band relative to loss at 1004 Hz is -2.0 dB to +5.5 dB.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1
 Issued 11/15/90 Effective January 1, 1991
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: Steve Jankin Title President
 AECA 11-18

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(G) Type C Transmission Specifications (Cont'd)

(3) C-Message Noise

The maximum C-Message Noise for the transmission patch at the route miles listed is less than or equal to:

<u>Route Miles</u>	<u>C-Message Noise*</u>	
	<u>Type C1</u>	<u>Type C2</u>
less than 50	32 dBrnCO	38 dBrnCO
51 to 100	33 dBrnCO	39 dBrnCO
101 to 200	35 dBrnCO	41 dBrnCO
201 to 400	37 dBrnCO	43 dBrnCO
401 to 1000	39 dBrnCO	45 dBrnCO

(4) C-Notch Noise

The maximum C-Notch Noise, utilizing a -16 dBm0 holding tone is less than or equal to 47 dBrnCO.

* For Feature Groups C and D only Type C2 will be provided. For Feature Groups A and B, Type C1 and C2 will be provided as set forth in Technical Reference TR-NPL-000334.

Pursuant to Orders NO. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: Alan Hunter Title President

AECA 11-19

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.2 Standard Transmission Specifications (Cont'd)

(G) Type C Transmission Specifications (Cont'd)

(5) Echo Control

Echo Control, identifies as Return Loss and expressed as Echo Return Loss and Singing Return Loss is dependent on the routing, i.e., whether the service is routed directly from the customer's point of termination (POT) to the end office or via an access tandem. It is equal to or greater than the following:

	<u>Echo Return Loss</u>	<u>Singing Return Loss</u>
POT to Access Tandem	13 dB	6 dB
POT to End Office		
- Direct	13 dB	6 dB
- Via Access Tandem (for FGB only)	8 dB	4 dB

11.1.3 Data Transmission Parameters

Two types of data Transmission Parameters, i.e., Type DA and Type DB, are provided for the Feature Group arrangements. Type DB is provided with Feature Groups A, B and C and also with Feature Group D when Feature Group D is directly routed to the end office. Type DA is only provided with Feature Group D and only when routed via an access tandem. Following are descriptions of each.

(A) Data Transmission Parameters Type DA

(1) Signal to C-Notched Noise Ratio

The Signal to C-Notched Noise Ratio is equal to or greater than 33 dB.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve Humler*Title President

AECA 11-20

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.3 Data Transmission Parameters (Cont'd)

(A) Data Transmission Parameters Type DA (Cont'd)

(2) Envelope Delay Distortion

The maximum Envelope Delay Distortion for the frequency banks and route miles specified is:

604 to 2804 Hz

less than 50 route miles	500 microseconds
equal to or greater than 50 route miles	900 microseconds

1004 to 2404 Hz

less than 50 route miles	200 microseconds
equal to or greater than 50 route miles	400 microseconds

(3) Impulse Noise Counts

The Impulse Noise Counts exceeding a 65 dBrnC0 threshold in 15 minutes is no more than 15 counts.

(4) Intermodulation Distortion

The Second Order (R2) and Third Order (R3) Intermodulation Distortion products are equal to or greater than:

Second Order (R2)	33 dB
Third Order (R3)	37 dB

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve Hunter*Title President

AECA 11-21

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.3 Data Transmission Parameters (Cont'd)

(A) Data Transmission Parameters Type DA (Cont'd)

(5) Phase Jitter

The Phase Jitter over the 4-300 Hz frequency band is less than or equal to 5° peak-to-peak.

(6) Frequency Shift

The maximum Frequency Shift does not exceed -2 to +2 Hz.

(B) Data Transmission Parameters Type DB

(1) Signal to C-Notched Noise Ratio

The signal to C-Notched Noise Ratio is equal to or greater than 30 dB.

(2) Envelope Delay Distortion

The maximum Envelope Delay Distortion for the frequency bands and route miles specified is:

604 to 2804 Hz

less than 50 route miles	800 microseconds
equal to or greater than 50 route miles	1000 microseconds

1004 to 2404 Hz

less than 50 route miles	320 microseconds
equal to or greater than 50 route miles	500 microseconds

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Brunler* Title President

AECA 11-22

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.1 Switched Access Service (Cont'd)

11.1.3 Data Transmission Parameters (Cont'd)

(B) Data Transmission Parameters Type DB (Cont'd)

(3) Impulse Noise Counts

The Impulse Noise counts exceeding a 67 dBrnC0 threshold in 15 minutes is no more than 15 counts.

(4) Intermodulation Distortion

The Second Order (R2) and Third Order (R3) Intermodulation Distortion products are equal to or greater than:

Second Order (R2)	31 dB
Third Order (R3)	34 dB

(5) Phase Jitter

The Phase Jitter over the 4-300 Hz frequency band is less than or equal to 7° peak-to-peak.

(6) Frequency Shift

The maximum Frequency Shift does not exceed -2 to +2 Hz.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *Steve J. Hansen* Title President

AECA 11-23

RECEIVED
NOV 21 1990
State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service

This section explains and lists the codes that the customer must specify when ordering Special Access Service. These codes provide a standardized means to relate the services being ordered to Special Access Service offerings contained in Section 7 preceding.

When ordering, the type of Special Access Service is described by two code sets, the Network Channel (NC) code and the Network Channel Interface (NCI) codes.

The Network Channel (NC) code consists of two elements. Element one is a Channel Service Code (character positions 1 and 2) that describes the channel service type in an abbreviated form. Element two is an Optional Feature Code (character positions 3 and 4) that identifies option codes available for each channel service code, such as C-conditioning or Improved Return Loss.

The Network Channel Interface (NCI) is used to identify interface specifications associated with a particular channel. This code describes the total wires, protocol, impedance, protocol options and transmission level point(s) reflecting physical and electrical characteristics between the Telephone Company and the customer.

On the following three (3) pages are examples which explain the specific characters of the codes and which reference matrices and charts used in developing the codes. Included in the matrices are Service Designator (SD) codes which are used to identify variations of service within service types. The SD and NC codes are displayed as components of the matrices designated as Technical Specifications packages in (A) through (E) following. Through the use of these matrices, SD codes may be converted to NC codes for service ordering purposes.

A chart is also provided in 11.3.2 following which contains information necessary to develop NCI codes.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1
Issued 11/15/90 Effective January 1, 1991
Issued By: Alaska Exchange Carriers Association, Inc.
By: *Steve A. Hummel* Title President
AECA 11-24

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

Comprehensive lists of allowed Network Channel (NC) and Network Channel Interface (NCI) codes are contained in Special Report SR-ISD-000307. However, not all services contained in this Special Report may be offered by the Telephone Company at this time.

Lastly, 11.3.2.C following provides a list of compatible Network Channel Interfaces inasmuch as the Network Channel Interfaces associated with a given service need not always be the same, but all must be compatible.

Example No. 1:

If the customer wishes to order a 4-wire voice grade circuit with 600 Ohms impedance, capable of data transmission, and with improved return loss, the customer might specify the following:

<u>NC</u>	<u>NCI</u>	<u>SECNCI</u>
LG-R	04DB2	04DA2-S
NC Code:		
LG =	Voice Grade Channel Service, VG6	
-R =	Improved Return Loss	
NCI Code:		
04 =	Number of physical wires at CDP	
DB =	Data stream in VF frequency band at the customer designated main terminal location	
2 =	600 Ohms impedance	
SECNCI (Secondary NCI Code):		
04 =	Number of physical wires at CDP	
DA =	Data stream in VG frequency at the customer designated secondary terminal location	
2 =	600 Ohms impedance	
S =	Sealing current option for 4-wire transmission	

In the above example the NCI (Network Channel Interface) code is the interface requested at the customer's POT (Point of Termination) and the SECNCI (Secondary Network Channel Interface) code represents the interface at the end office serving the End User.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Dumbler* Title President

AECA 11-25

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

Example No. 2:

If the customer wishes to order a FX circuit to a station, with 600 Ohms impedance, loop start signaling, which is 4-wire at the CDP and 2-wire at the end-user, the customer might specify:

<u>NC</u>	<u>NCI</u>	<u>SECNCI</u>
LC--	04L02	02LS2
NC Code:		
LC =	Voice Grade Channel Service, VG2	
-- =	No Optional Features	
NCI Code:		
04 =	Number of physical wires at CDP	
L0 =	Loop start, loop signaling - open end	
2 =	600 Ohms impedance	
SECNCI (Secondary NCI Code):		
02 =	Number of physical wires at CDP	
LS =	Loop start signaling - closed end	
2 =	600 Ohms impedance	

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: Steve Humble Title President

AECA 11-26

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

Example No. 3:

If the customer wishes to order a 1.544 Mbps Hi-cap facility with no channel options such as CO multiplexing, the customer might specify the following:

<u>NC</u>	<u>NCI</u>	<u>SECNCI</u>
HC--	04DS9-15	04DS9-15

NC Code:

HC = High Capacity Channel Service, HC1
 -- = No Optional Features

NCI, SECNCI Code:

04 = Number of physical wires at CDP
 DS = Digital hierarchy interface
 9 = 100 Ohms impedance
 15 = 1.544 Mbps (DS1) format

The preceding three examples use information contained in Special Report SR-ISD-000307.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: Steve Danley Title President

AECA 11-27

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes

In order to determine the NC code appropriate for the service to be ordered, the type of Special Access Service the customer wishes must be identified. This identification is accomplished by a Service Designator (SD) code. The broad categories of Service Designator codes (e.g., VG, etc.) are set forth in Section 7 preceding. Variations within service type (e.g., VG1, etc.) are described in the various Technical Publications cited in (A) through (E) following. Having determined the specific service type to be ordered and its SD code, and having used the appropriate Technical Publication, the customer should match the SD code to the NC code using the following matrices. Once the NC code has been determined the Network Channel Interface (NCI) code may be developed using the information set forth in 11.2.1 following and the guidelines concerning specific parameters available for each service type as set forth in the specified Technical Publication.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: *[Signature]*Title President

AECA 11-28

RECEIVED
NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes

(A) Technical Specifications Packages Voice Grade Service

SD Code	C*	Package VG-														W
		1	2	3	4	5	6	7	8	9	10	11	12	LR	SE	
NC Code	LQ	LB	LC	LD	LE	LF	LG	LH	LJ	LK	LN	LP	LR	SE		
<u>Parameter</u>																
Attenuation																
Distortion	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
C-Message Noise	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Echo Control	X	X	X	X		X		X	X			X	X	X		
Envelope Delay																
Distortion	X						X	X	X	X	X	X	X	X		
Frequency Shift	X						X	X	X	X	X	X	X	X		
Impulse Noise	X					X	X	X	X	X	X	X	X	X		
Intermodulation																
Distortion	X						X	X	X	X	X	X		X		
Loss Deviation	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
Phase Hits, Gain Hits, and Dropouts																
Phase Jitter	X						X	X	X	X	X	X		X		
Signal-to-C																
Message Noise					X											
Signal-to-C																
Notch Noise	X					X	X	X	X	X	X	X	X	X		

The technical specifications for these parameters (except for dropouts, phase hits, and gain hits) are described in Technical References TR-NPL-000334 and TR-NPL-000335. The technical specifications for dropouts, phase hits, and gain hits are described in Technical Reference PUB41004, Table 4.

* The desired parameters are selected by the customer from the list of available parameters.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1
 Issued 11/15/90 Effective January 1, 1991
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: [Signature] Title President
 AECA 11-29

RECEIVED
 NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

		Package VG-														
SD Code	C*	1	2	3	4	5	6	7	8	9	10	11	12	W		
NC Code	LQ	LB	LC	LD	LE	LF	LG	LH	LJ	LK	LN	LP	LR	SE		

Optional Features and Functions

Central Office														
Bridging Capability	X		X			X	X				X	X	X	
Conditioning:														
. C-Type	X					X	X	X	X	X	X			
. Improved Attenuation Distortion	X					X	X	X	X	X	X			
. Improved Envelope Delay Distortion	X					X	X	X	X	X	X			
. Data Capability	X						X	X			X			
Improved Two-Wire Voice Transmission														X
Signaling Capability	X	X	X	X				X	X	X				
Central Office Multiplexing	X						X							
Sealing Current	X						X							
Telephoto Capability	X											X		
Customer Specified Premises Receive Level	X		X	X				X	X	X				
Improved Return Loss for Effective Four-Wire Transmission	X	X	X	X	X	X	X	X	X	X	X	X	X	X
For Effective Two-Wire Transmission	X		X	X				X						
PPSN Interface Arrangement	X									X				
Selective Signaling Arrangement	X		X			X	X				X			
Transfer Arrangement	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1
 Issued 11/15/90 Effective January 1, 1991
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: [Signature] Title President
 AECA 11-30

RECEIVED

APR 30 1997

ALASKA PUBLIC UTILITIES COMM.

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

(B) Technical Specifications Packages Digital Data Service

SD Code NC Code	Package						D6 YN
	D1 XA	D2 XB	D3 XG	D4 XH	D5 XE		

Parameter/Hubbed

Error-Free Seconds	X	X	X	X	X	X
--------------------	---	---	---	---	---	---

Optional Features
and Functions/Hubbed

Central Office Bridging Capability	X	X	X	X	X	X
---------------------------------------	---	---	---	---	---	---

Transfer Arrangement	X	X	X	X	X	X
----------------------	---	---	---	---	---	---

PPSN Interface Transfer Arrangement	X	X	X	X	X	X
--	---	---	---	---	---	---

The Telephone Company will provide a channel capable of meeting a monthly average performance equal to or greater than 99.875% error-free seconds (if provided through a Digital Data hub) while the channel is in service, if it is measured through a CSU equivalent which is designed, manufactured, and maintained to conform with the specifications contained in Technical Reference PUB 62310.

Optional Features and Functions/Non-Hubbed (N)

Public Packet Data Arrangement	X	X	(N)
--------------------------------	---	---	-----

Voltages which are compatible with Digital Data Service are delineated in Technical Reference PUB TR-NWT-000341.11

Tariff Advice No. 34 Effective: June 27, 1997

Issued: _____
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: Keith A. Steele Title: President

RECEIVED

JUN 11 2009

STATE OF ALASKA
REGULATORY COMMISSION OF ALASKA

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

C. Technical Specifications Packages High Capacity Service

SD Code	HBO	HC1	Package				HC4
			HC1C	HC2	HC3	HC4	
NC Code	HS	HC	HD	HE	HF	HG	
Parameters							
Error-Free Seconds		X					
Optional Features and Functions							
Automatic Loop Transfer		X					
Central Office							
Multiplexing:							
DS4 to DS1						X	
DS3 to DS1					X		
DS2 to DS1				X			
DS1C to DS1			X				
DS1 to Voice		X					
DS1 to DSO		X					
DSO to Subrate*	X						
Transfer Arrangement		X					

A channel with technical specifications package HC1 will be capable of an error-free second performance of 98.75% over a continuous 24 hour period as measured at the 1.544 Mbps rate through a CSU equivalent which is designed, manufactured, and maintained to conform with the specifications contained in Technical Reference GR-342-CORE.

(C)

* Available only on a channel of 1.544 Mbps facility to a Telephone Company hub.

Tariff Advice No. 71

Effective:

August 7, 2009

Issued:

Issued By: Alaska Exchange Carriers Association, Inc

By: Judith A. Colbert

Title:

Executive Director

RECEIVED

JUN 11 2009

STATE OF ALASKA
TELECOMMUNICATIONS COMMISSION

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

C.1 Technical Specifications Packages Synchronous Optical Channel Service

		<u>Package</u>	
	SD Code	OC3	OC12
	NC Code	OB	OD
Parameters			
Error-Free Seconds		X	X
Optional Features and Functions			
Customer Premises Multiplexing:			
OC12 to OC3			X
OC12 to OC3c			X
OC12 to DS3			X
OC12 to DS1			X
OC3 to STS-1	X		
OC3 to DS3	X		
OC3 to DS1	X		
Central Office Multiplexing:			
OC12 to OC3			X
OC12 to OC3c			X
OC3 to DS3	X		
OC3 to DS1	X		

Technical specifications are delineated in Technical Reference GR-253-CORE, GR-1374-CORE, ANSI T1.102-1993 and ANSI T1.105-2001.

Tariff Advice No. 71

Effective:

August 7, 2009

Issued:
 Issued By: Alaska Exchange Carriers Association, Inc
 By: Judith A. Colbert *Judith A. Colbert*

Title: Executive Director

RECEIVED

SEP 23 1991

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

(D) Technical Specifications Packages Program
Audio Service

SD Code NC Code	Package				
	APC* PQ	AP1 PE	AP2 PF	AP3 PJ	AP4 PK
<u>Parameter</u>					
Actual Measured Loss	X	X	X	X	X
Amplitude Tracking	X				
Crosstalk	X	X	X	X	X
Distortion Tracking	X				
Gain/Frequency Distortion	X	X	X	X	X
Group Delay	X				
Noise	X	X	X	X	X
Phrase Tracking	X				
Short-Term Gain					
Stability	X				
Short-Term Loss	X				
Total Distortion	X	X	X	X	X
<u>Optional Features and Functions</u>					
Central Office Bridging Capability	X	X	X	X	X
Gain Conditioning	X	X	X	X	X
Stereo	X				X

The technical specifications are described in
Technical Reference TR-NPL-000337 and (C)
associated Addendum.

* The desired parameters are selected by the customer from the
list of available parameters.

Pursuant to Letter Order Dated July 15, 1991.

Tariff Advise No. 3 Effective: July 15, 1991

Issued: September 24, 1991
Issued by: Alaska Exchange Carriers Association, Inc.
By: [Signature] Title: President

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

(E) Technical Specifications Packages Video Service

SD Code NC Code	Package		
	TVC* TQ	TV1 TV	TV2 TW
<u>Video Parameters</u>			
Insertion Gain	X	X	X
Field-Time Distortion	X	X	X
Line-Time Distortion	X	X	X
Short-Time Distortion	X	X	X
Chrominance-Luminance Gain Inequality	X	X	X
Chrominance-Luminance Delay Inequality	X	X	X
Amplitude/Frequency Characteristic	X	X	X
Luminance Non-Linear Distortion	X	X	X
Chrominance Non-Linear Gain Distortion	X	X	X
Chrominance Non-Linear Phase Distortion	X	X	X
Transient Synchronizing Signal Non-Linearty	X	X	X
Dynamic Gain Distortion			
- Picture Signal	X	X	X
- Synchronizing S ignal	X	X	X
Differential Gain	X	X	X
Differential Phase	X	X	X
Chrominance-Luminance Intermodulation	X	X	X

* The desired parameters are selected by the customer from the list of available parameters.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Johnson*

Title President

AECA 11-34

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.1 Network Channel (NC) Codes (Cont'd)

(E) Technical Specifications Packages Video Service
(Continued)

SD Code NC Code	Package		
	TVC*	TV1	TV2
	TQ	TV	TW
<u>Audio Channel Parameters</u>			
<u>Associated with Video Service</u>			
Insertion Gain	X	X	X
Amplitude/Frequency Characteristic	X	X	X
Total Harmonic Distortion and Noise	X	X	X
Maximum Steady-State Test Levels	X	X	X
Gain Differential Between Channels	X	X	
Phase Differential Between Channels	X	X	
Crosstalk	X	X	X
Audio-To-Video Time Differential	X	X	X

The technical specifications are described in Technical Reference TR-NPL-000338.

* The desired parameters are selected by the customer from the list of available parameters.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Steve Hummer

Title President

AECA 11-35

RECEIVED
 NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes

The electrical interface with the Telephone Company for Special Access Services, is defined by an interface code. There are interface codes for both the customer designated premises and the point of termination.

(A) Parameter Codes and Options

Parameter

<u>Code</u>	<u>Option</u>	<u>Definition</u>
AB -		accepts 20 Hz ringing signal at customer's point of termination
AC -		accepts 20 Hz ringing signal at customer's end user's point of termination
AH -		analog high capacity interface
	- B	60 kHz to 108 kHz (12 channels)
	- C	312 kHz to 552 kHz (60 channels)
	- D	564 kHz to 3084 kHz (600 channels)
CT -		Centrex Tie Trunk Termination
DA -		data stream in VF frequency band at customer's end user's point of termination
DB -		data stream in VF frequency band at customer's point of termination
DC -		direct current or voltage
	- 1	monitoring interface with series RC combination (McCulloh format)
	- 2	Telephone Company energized alarm channel

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: Steve Humlen Title President

AECA 11-36

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

- 11. Access Service Interfaces and Transmission Specifications (Cont'd)
- 11.2 Special Access Service (Cont'd)
- 11.2.2 Network Channel Interface (NCI) Codes (Cont'd)
- (A) Parameter Codes and Options (Cont'd)

<u>Parameter</u>		<u>Definition</u>
<u>Code</u>	<u>Option</u>	
DS	-	digital hierarchy interface
	- 15	1.544 Mbps (DS1) format per Bellcore GR-54 (C) plus D4
	- 15E	8-bit PCM encoded in one 64 Kbps of the DS1 signal
	- 15F	8-bit PCM encoded in two 64 Kbps of the DS1 signal
	- 15G	8-bit PCM encoded in three 64 Kbps of the DS1 signal
	- 15H	14/11-bit PCM encoded in six 64 Kbps of the DS1 signal
	- 15J	1.544 Mbps format per Bellcore GR-54 (C)
	- 15K	1.544 Mbps format per Bellcore GR-54 plus extended framing format (C)
	- 15L	1.544 Mbps (DS1) with SF signaling
	- 27	274.176 Mbps (DS4)
	- 27L	274.176 Mbps (DS4) with SF signaling
	- 31	3.152 Mbps (DS1C)
	- 31L	3.152 Mbps (DS1C) with SF signaling
	- 44	44.736 Mbps (DS3)
	- 44L	44.736 Mbps (DS3) with SF signaling
	- 63	6.312 Mbps (DS2)
	- 63L	6.312 Mbps (DS2) with SF signaling
DU	-	digital access interface
	- 24	2.4 Kbps
	- 48	4.8 Kbps
	- 19	19.2 Kbps (C)
	- 56	56.0 Kbps
	- 96	9.6 Kbps
	- 64	64.0 Kbps (C)
	- A	1.544 Mbps format per Bellcore GR-54 (C)
	- B	1.544 Mbps format per Bellcore GR-54 plus D4 (C)
	- C	1.544 Mbps format per Bellcore GR-54 plus extended framing format (C)
DX	-	duplex signaling interface at customer's point of termination
DY	-	duplex signaling interface at customer's end user's point of termination (D)

Tariff Advice No. 31 Effective: July 29, 1996

Issued: _____
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: *Keith A. Steuber* Title: President

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(A) Parameter Codes and Options (Cont'd)

Parameter

<u>Code</u>	<u>Option</u>	<u>Definition</u>
EA	E	Type I E&M Lead Signaling. Customer at POT or customer's end user at POT originates on E Lead.
EA	M	Type I E&M Lead Signaling. Customer at POT or customer's end user at POT originates on M Lead.
EB	E	Type II E&M Lead Signaling. Customer at POT or customer's end user at POT originates on E Lead.
EB	M	Type II E&M Lead Signaling. Customer at POT or customer's end user at POT originates on M Lead.
EC		Type III E&M signaling at customer POT
EX	A	tandem channel unit signaling for loop start or ground start and customer supplies open end (dial tone, etc.) functions.
EX	B	tandem channel unit signaling for loop start or ground start and customer supplies closed end (dial pulsing, etc.) functions.
GO		ground start loop signaling - open end function by customer or customer's end user
GS		ground start loop signaling - closed end function by customer or customer's end user
IA		E.I.A. (25 pin RS-232)
LA		end user loop start loop signaling-Type A OPS registered port open end
LB		end user loop start loop signaling-Type B OPS registered port open end
LC		end user loop start loop signaling-Type C OPS registered port open end

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: Steve Dunlop Title President

AECA 11-38

RECEIVED

JUN 11 2009

STATE OF ALASKA
REGULATORY COMMISSION OF ALASKA

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

A. Parameter Codes and Options (Cont'd)

- LO loop start loop signaling - open end function by customer or customer's end user
- LR 20 Hz automatic ringdown interface at customer with Telephone Company provided PLAR
- LS loop start loop signaling - closed end function by customer or customer's end user
- NO no signaling interface, transmission only

Parameter

<u>Code</u>	<u>Option</u>	<u>Definition</u>
PG		program transmission - no dc signaling
	1	nominal frequency from 50 to 15000 Hz
	3	nominal frequency from 200 to 3500 Hz
	5	nominal frequency from 100 to 5000 Hz
	8	nominal frequency from 50 to 8000 Hz
PR		protective relaying*
RV	0	reverse battery signaling, one way operation, originate by customer
	T	reverse battery signaling, one way operation, terminate function by customer or customer's end user
SF		single frequency signaling with VF band at either customer POT or customer's end user POT
	2	20.0 milliamperes
	3	3.0 milliamperes
	6	62.5 milliamperes
SO		SONET Optical (L)(N)
	AB	Long Range Multilongitudal Mode (LR1-MLM) Bidirectional Ring
	AU	LR1-MLM Unidirectional Ring
	BB	Long Range Single Longitudal Mode (LR1-SLM) Bidirectional Ring

(N)

(L) Text relocated to Original Sheet No. 260.1

Tariff Advice No. 71

Effective:

August 7, 2009

Issued:

Issued By: Alaska Exchange Carriers Association, Inc

By: Judith A. Colbert

Judith A. Colbert

Title:

Executive Director

RECEIVED

JUN 11 2009

STATE OF ALASKA
REGULATORY COMMISSION OF ALASKA

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

A. Parameter Codes and Options (Cont'd) (N)

Parameter

<u>Code</u>	<u>Option</u>	<u>Definition</u>
SO		SONET Optical (Cont'd)
	BU	LR1-MLM
	CB	Intermediate Range Multilongitudinal Mode (IR1-MLM) Bidirectional Ring
	CU	IR1-MLM Unidirectional Ring
	DB	Intermediate Range Single Longitudinal Mode (IR1-SLM) Bidirectional Ring
	DU	IR1-SLM Unidirectional Ring
	EB	Short Range Multilongitudinal Mode Light Emitting Diode (SR-MLM/LED) Bidirectional Ring
	EU	SR-MLM/LED Unidirectional Ring
	FB	Short Range Multilongitudinal Mode (SR-MLM) Bidirectional Ring
	FU	SR-MLM Unidirectional Ring
ST		Synchronous Transmission Signal (STS)
	A	STS1
TV		television interface (L)
	1	combined (diplexed) video and one audio signal
	2	combined (diplexed) video and one audio signals

(L) Text relocated from Sheet No 260

Tariff Advice No. 71

Effective:

August 7, 2009

Issued:
 Issued By: Alaska Exchange Carriers Association, Inc
 By: Judith A. Colbert *Judith A. Colbert*

Title: Executive Director

RECEIVED
 NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(A) Parameter Codes and Options (Continued)

- 5 video plus one (or two) audio 5 kHz signal(s) or one (or two) two wire
- 15 video plus one (or two) audio 15 kHz signal(s)

* Available only for the transmission of audio tone protective relaying signals used in the protection of electric power systems during fault conditions.

(B) Impedance

The nominal reference impedance with which the channel will be terminated for the purpose of evaluating transmission performance:

<u>Value (ohms)</u>	<u>Code(s)</u>
110	0
150	1
600	2
900	3*
135	5
75	6
124	7
Variable	8
100	9

* For those interface codes with a 4-wire transmission path at the customer designated POT, rather than a standard 900 ohm impedance the code (3) denotes a customer provided transmission equipment termination. Such terminations were provided to customers in accordance with the FCC Docket No. 20099 Settlement Agreement.

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1
 Issued 11/15/90 Effective January 1, 1991
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: Steve Humbley Title President
 AECA 11-40

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces

(1) Voice Grade

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
2AB2	2AC2	2DB2	2DA2	2LR2	2LR2
2AB3	2AC2	2DB3	2DA2	2LR3	2LR2
2CT3	2DY2	2DX3	2LA2	2LS	2GS
	4DS8		2LB2		2LS
	4DX2		2LC2		4GS
	4DX3		2LO3		4LS
	4DY2		2LS2		
	4EA2-E		2LS3	2LS2	2LA2
	4EA2-M				2LB2
	4SF2	2GO2	2GS2		2LC2
	4SF3		2GS3		
	6DX2			2LS3	2LA2
	6DY2	2GO3	2GS2		2LB2
	6DY3		2GS3		2LC2
	6EA2-E				
	6EA2-M	2GS	2GS	2NO2	2DA2
	6EB2-E		2LS		2NO2
	6EB2-M		4GS		
	6EB3-E		4LS	2NO3	2NO2
	8EB2-E				2PR2
	8EB2-M	2LO2	2LS2		
	8EC2		2LS3	2TF3	2TF2
	9DY2				
	9DY3	2LO3	2LS2		
	9EA2		2LS3		
	9EA3				

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: Steve Hunter Title President

AECA 11-41

RECEIVED
NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>	<u>Compatible CIs</u>	<u>Compatible CIs</u>	<u>Compatible CIs</u>
4AB2	2AC2		
	4AB2		
	4AC2		
	4SF2		
4AB3	2AC2		
	4AC2		
	4SF2		
4AC2	2AC2		
	4AC2		
		4DS8-	2AC2
			2DA2
			2DY2
			2GO2
4DA2	4DA2		2GO3
			2GS2
4DB2	2DA2		2GS3
	2NO2		2LA2
	2PR2		2LB2
	4DA2		2LC2
	4DB2		2LO2
	4NO2		2LO3
	4PR2		2LR2
	6DA2		2LS2
			2LS3
4DD3	2DE2		2NO2
	4DE2		2PR2
			2RV2-T
			2TF2
			4AC2
			4DA2
			4DE2
			4DX2
			4DX3
			4DY2
			4EA2-E
			4EA2-M
		4DS8-	4DG2
			4LR2
			4LS2
			4NO2
			4PR2
			4RV2-T
			4SF2
			4SF3
			4TF2
			6DA2
			6DY2
			6DY3
			6EA2-E
			6EA2-M
			6EB2-E
			6EB2-M
			6GS2
			6LS2
			8EB2-E
			8EB2-M
			9DY2
			9DY3
			9EA2
			9EA3

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Steve Dumbler

Title

President

AECA 11-42

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
 Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
4DX2	2DY2	4DX2	8EB2-E	4DX3	6DY2
	2LA2		8EB2-M		6DY3
	2LB2		9DY2		6EA2-E
	2LC2		9DY3		6EA2-M
	2LO3		9EA2		6EB2-E
	2LS2		9EA3		6EB2-M
	2LS3				6LS2
	2RV2-T	4DX3	2DY2		8EB2-E
	4DX2		2LA2		8EB2-M
	4DY2		2LB2		9DY2
	4EA2-E		2LC2		9DY3
	4EA2-M		2LO3		9EA2
	4LS2		2LS2		9EA3
	4RV2-T		2LS3		
	4SF2		2RV2-T	4DY2	2DY2
	4SF3		4DX2		4DY2
	6DY2		4DX3		
	6DY3		4DY2		
	6EA2-E		4EA2-E		
	6EA2-M		4EA2-M		
	6EB2-E		4LS2		
	6EB2-M		4RV2-T		
	6LS2		4SF2		
			4SF3		

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve J. Hambley* Title President

AECA 11-43

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

Compatible CIs		Compatible CIs		Compatible CIs	
4EA2-E	2DY2	4EA3-E	2DY2	4G02	2G02
	4DY2		4DY2		2G03
	4EA2-E		4EA2-E		2GS2
	4EA2-M		4EA2-M		2GS3
	4SF2		4SF2		4GS2
	6DY2		6DY2		4SF2
	6DY3		6DY3		6GS2
	6EB2-E		6EA2-E		
	6EB2-M		6EA2-M	4G03	2G02
	8EB2-E		6EB2-E		2GS2
	8EB2-M		6EB2-M		2GS3
	9DY2		8EB2-E		4GS2
	9DY3		8EB2-M		4SF2
			9DY2		6GS2
4EA2-M	2DY2		9DY3		
	4DY2		9EA2		
	4EA2-M		9EA3	4GS	2GS
	4SF2				2LS
	6DY2				4GS
	6DY3				4LS
	6EB2-E				
	6EB2-M				
	8EB2-E				
	8EB2-M				
	9DY2				
	9DY3				

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Humler* Title President

AECA 11-44

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
 Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
4LO2	2LS2	4LS3	2LA2	4SF2	2LO3
	2LS3		2LB2		2LR2
	4LS2		2LC2		2LS2
	4SF2		2LO2		2LS3
	6LS2		2LO3		2RV2-T
			4SF2		4AC2
4LO3	2LS2				4DY2
	2LS3	4NO2	2DA2		4LS2
	4LS2		2DE2		4RV2-T
	4SF2		2NO2		4SF2
	6LS2		4DA2		6DY2
			4DE2		6DY3
4LR2	2LR2		4NO2		6GS2
	4LR2		6DA2		9DY2
	4SF2				9DY3
		4RV2-0	2RV2-T		
4LR3	2LR2		4RV2-T	4SF3	2DY2
	4LR2		4SF2		2G03
	4SF2				2GS2
					2GS3
4LS	2GS	4SF2	2AC2		2LA2
	2LS		2DY2		2LB2
	4GS		2GS2		2LC2
	4LS		2GS3		2LO3
			2LA2		2LR2
4LS2	2LA2		2LB2		
	2LB2		2LC2		
	2LC2				
	2LO2				
	2LO3				

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: *Steve Hunter* Title President

RECEIVED
NOV 21 1990
 State of Alaska
 Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
4SF3	2LS2	6DA	4DA2	6DY3	2DY2
	2LS3		6DA2		4DY2
	2RV2-T				6DY2
	4DY2	6DX2	2DY2		6DY3
	4EA2-E		4DY2		
	4EA2-M		4EA2-E	6EA2-E	2AC2
	4GS2				
	4LR2		4EA2-M		2DY2
	4LS2		4SF2		2LA2
	4RV2-T		6DY2		2LB2
	4SF2		6DY3		2LC2
	4SF3		6EA2-E		2LO3
	6DY2		6EA2-M		2LS2
	6DY3		6EB2-E		2LS3
	6EB2-E		6EB2-M		2RV2-T
	6EB2-M		8EB2-E		4AC2
	6GS2		8EB2-M		4DY2
	6LS2		9DY2		4EA2-E
	9DY2		9DY3		4EA2-M
	9DY3		9EA2		4LS2
	9EA2		9EA3		4RV2-T
	9EA3				4SF2
		6DY2	2DY2		4SF3
4TF2	2TF2		4DY2		6DY2
	4TF2		6DY2		6DY3
					6EA2-E
					6EA2-M

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: Steve Jumbly Title President

AECA 11-46

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
 Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
6EA2-E	6EB2-E	6EA2-M	6DY2	6EB-3E	2DY2
	6EB2-M		6DY3		4DY2
	6LS2		6EA2-M		4EA2-E
	8EB2-E		6EB2-E		4EA2-M
	8EB2-M		6EB2-M		4SF2
	9DY2		6LS2		6DY2
	9DY3		8EB2-E		6DY3
			8EB2-M		6EA2-E
6EA2-M	2AC2		9DY2		6EA2-M
	2DY2		9DY3		8EB2-E
	2LA2				8EB2-M
	2LB2	6EB2-E	2DY2		9DY2
	2LC2		4DY2		9DY3
	2LO3		4SF2		9EA2
	2LS2		6DY2		9EA3
	2LS3		6DY3		
	2RV2-T		6EB2-E	6EX2-A	2GS2
	4AC2		6EB2-M		2GS3
	4DY2		9DY2		2LS2
	4EA2-E		9DY3		2LS3
	4EA2-M				4GS2
	4RLS2	6EB2-M	SDY2		4LS2
	4RV2-T		4DY2		4SF2
	4SF2		4SF2		6GS2
	4SF3		6DY2		6LS2
			6DY3		
			6EB2-M		
			9DY2		
			9DY3		

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By: Steve Hamby Title President

AECA 11-47

RECEIVED

NOV 21 1990

State of Alaska

Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
6EX2-B	2G03	8EB2-E	2AC2	8EB2-M	2AC2
	2LA2		2DY2		2DY2
	2LB2		2LA2		2LA2
	2LC2		2LB2		2LB2
	2LO2		2LC2		2LC2
	2LO3		2LO3		2LO3
	2LR2		2LS2		2LS2
	4LR2		2LS3		2LS3
	4SF2		2RV2-T		2RV2-T
			4AC2		4AC2
6G02	2G02		4DY2		4DY2
	2GS2		4LS2		4LS2
	2GS3		4RV2-T		4RV2-T
	4GS2		4SF2		4SF2
	4SF2		4SF3		4SF3
	6GS2		6DY2		6DY2
			6DY3		6DY3
6LO2	2LS2		6EB2-E		6EB2-E
	2LS3		6EB2-M		6EB2-M
	4LS2		6LS2		6LS2
	4SF2		8EB2-E		8EB2-M
	6LS2		8EB2-M		9DY2
			9DY2		9DY3
6LS2	2LA2		9DY3		
	2LB2				
	2LC2				
	2LO2				
	2LO3				
	4SF2				

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Steve J. Smith

Title

President

AECA 11-48

RECEIVED

NOV 21 1990

State of Alaska
Public Utilities Commission

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(1) Voice Grade (Cont'd)

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
8EC2	2DY2	9DY2	2DY2	9EA3	2DY2
	4DY2		4DY2		4DY2
	4EA2-E		6DY2		4EA2-E
	4EA2-M		6DY3		4EA2-M
	4SF2		9DY2		6DY2
	6DY2				6DY3
	6DY3	9DY3	2DY2		6EA2-E
	6EA2-E		4DY2		6EA2-M
	6EA2-M		6DY2		6EB2-E
	6EB2-E		6DY3		6EB2-M
	6EB2-M		9DY2		8EB2-E
	8EB2-E		9DY3		8EB2-M
	8EB2-M				9DY2
	9DY2	9EA2	2DY2		9DY3
	9DY3		4DY2		9EA3
	9EA2		4EA2-E		
	9EA3		4EA2-M		
			6DY2		
			6DY3		
			6EA2-E		
			6EA2-M		
			6EB2-E		
			6EB2-M		
			8EB2-E		
			8EB2-M		
			9DY2		
			9DY3		
			9EA2		
			9EA3		

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1
 Issued 11/15/90 Effective January 1, 1991
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: Steve J. Jambler Title President
 AECA 11-49

RECEIVED

TELEPHONE EXCHANGE CARRIERS OF ALASKA

NOV 21 1990
State of Alaska
Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(2) Program Audio

<u>Compatible CIs</u>		<u>Compatible CIs</u>	
2PG2-1	2PG1-1	4DS8-15E	2PG1-3
	2PG2-1		2PG2-3
2PG2-3	2PG1-3	4DS8-15F	2PG1-5
	2PG2-3		2PG2-5
2PG2-5	2PG1-5	4DS8-15G	2PG1-8
	2PG2-5		2PG2-8
2PG2-8	2PG1-8	4DA8-15H	2PG1-1
	2PG2-8		2PG2-1

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90 Effective January 1, 1991Issued By: Alaska Exchange Carriers Association, Inc.By: Steve Jumbly Title President

AECA 11-50

RECEIVED
NOV 21 1990

TELEPHONE EXCHANGE CARRIERS OF ALASKA

State of Alaska
Public Utilities Commission

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(3) Video

<u>Compatible CIs</u>		<u>Compatible CIs</u>	
2TV6-1	4TV6-15 4TV7-15	4TV7-5	4TV6-5 4TV7-5
2TV6-2	6TV6-15 6TV7-15	4TV7-15	4TV6-15 4TV7-15
2TV7-1	4TV6-15 4TV7-15	6TV6-5	6TV6-5 6TV7-5
2TV7-2	6TV6-15 6TV7-15	6TV6-15	6TV6-15 6TV7-15
4TV6-5	4TV6-5 4TV7-5	6TV7-5	6TV6-5 6TV7-5
4TV6-15	4TV6-15 4TV7-15	6TV7-15	6TV6-15 6TV7-15

Pursuant to Orders No. 6 & 7 in Docket U-90-26

Tariff Advice No. 1

Issued 11/15/90

Effective January 1, 1991

Issued By: Alaska Exchange Carriers Association, Inc.

By:

Title President

AECA 11-51

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

(C) Compatible Network Channel Interfaces (Cont'd)

(4) Digital Data

<u>Compatible CIs</u>		<u>Compatible CIs</u>		<u>Compatible CIs</u>	
4DS8-15	4DS8-15+	4DU5-24	4DU5-24	6DU5-24	6DU5-24
	4DU5-24				
	4DU5-48	4DU5-48	4DU5-48	6DU5-48	6DU5-48
	4DU5-56				
	4DU5-96	4DU5-96	4DU5-96	6DU5-56	6DU5-56
	6DU5-24				(N)
	6DU5-48				
	6DU5-96	4DU8-56	4DU5-56	6DU5-96	6DU5-96

+ Available only as a cross connect of two digital channels at appropriate digital speeds at a Telephone Company hub.

Tariff Advice No. 31 Effective: July 29, 1996

Issued: _____
 Issued By: Alaska Exchange Carriers Association, Inc.
 By: *Keith A. Steele* Title: President

RECEIVED

JUN 11 2009

STATE OF ALASKA
REGULATORY COMMISSION OF ALASKA

TELEPHONE EXCHANGE CARRIERS OF ALASKA

ACCESS SERVICES

11. Access Service Interfaces and Transmission Specifications (Cont'd)

11.2 Special Access Service (Cont'd)

11.2.2 Network Channel Interface (NCI) Codes (Cont'd)

C. Compatible Network Channel Interfaces (Cont'd)

5. High Capacity

<u>Compatible CIs</u>		<u>Compatible CIs</u>	
4DSO-63	4DSO-63 4DU8-A, B or C 6DU8-A, B or C	4DS8-15J	4DU8-A 6DU8-A
4DS6-27	4DS6-27 4DU8-A, B or C 6DU8-A, B or C	4DS8-15K	4DU8-B 4DU8-C 6DU8-B 6DU8-C
4DS6-44	4DS6-44 4DU8-A, B or C 6DU8-A, B or C	4DS8-31	4DS8-31 4DU8-A, B or C 6DU8-A, B or C
4DS8-15	4DS8-15+ 4DU8-B 6DU8-8	4DU8-A, B or C	4DU8-A, B or C

6. Synchronous Optical Channel Service

(N)

<u>Compatible CIs</u>		<u>Compatible CIs</u>	
4DS9-1S	4DU9-1S	2SOF-A	2SOF-A
4DS9-1K	4DU9-1K	2SOF-B	2SOF-B
		2SOF-C	2SOF-C
		2SOF-D	2SOF-D
		2SOF-E	2SOF-E
		2SOF-F	2SOF-F

The following network channel interfaces (NCIs) define the bit rates that are available for a synchronous optical channel:

<u>NCI</u>	<u>Bit Rate</u>
FCF-B	155.52 Mbps (OC3, OC3c)
FCF-D	622.08 Mbps (OC12)

(N)

+ Available only as a cross connect of two individual channels of 1.544 Mbps facilities at a Telephone Company hub.

Tariff Advice No. 71

Effective: August 7, 2009

Issued: _____
 Issued By: Alaska Exchange Carriers Association, Inc
 By: Judith A. Colbert *Judith A. Colbert* Title: Executive Director